ICBA SH, Stainless

Height: 32.8" Width: 11.8" Depth: 23.2" (83.3cm) (30.0cm) (58.9cm)





- Sleek modernized design language, with rounded angles on the corners and trunk
- Digital readout displays in English, Spanish, or French ---for easier programming and control--- and can show either 'Standard' or Metric measurements. Digital readout also shows machine status, and targeted advertising messages can be programmed for display.
- BUNN Infusion Series technology allows for multiple recipes from one footprint --with three brew buttons and three batch sizes
- Energy-saver mode reduces tank temperature during idle periods
- The exclusive Peak Extraction® Sprayhead provides improved uniformity of extraction and greater resistance to limescale buildup.
- Electronic funnel lock prevents removal of each brew funnel until drip- through is complete
- USB programming capable
- Brew counter keeps track of how many batches are brewed
- Pre-infusion and pulse brew for maximum flavor extraction. Cold brew lockout & digital temperature control further ensure top-notch brewing.
- New Soft Heat® servers [sold separately] are ergonomic, lighter weight, energy
 efficient and now offer programmable recipe/batch based holding times and
 temperatures, alerting staff when freshness has expired or server is empty

Agency:

(

Specifications

Product #: 51100.0500 Faucet: Side

Water Access: Plumbed Legs: 4" Satin Nickel Legs

Finish: Stainless
Funnel: Smart Funnel

Additional Features

BrewWISE

Electrical & Capacity

Volts*	ts* Amps Watte		ts Cord Plug T		8oz cups/hr Input H²O 236ml cups/hr Temp.		Phase	# Wires plus Ground	Hertz
220-240	13.2-14.1	2900-3400	Yes	EURO 16A	163	60°F (15.5°C)	1	2	50-60

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

Plumbing Requirements


PSI	kPa	Fitting Supplied	Water Flow Required (GPM)				
20-90	138-621	3/8" Male Flare Fitting	1.00				


CAD Drawings


2D	Revit	KLC
•		

MARNING:









Unit				Shipping				
	Height	Width	Depth	Height	Width	Depth	Weight	Volume
English	32.8 in.	11.8 in.	23.2 in.	37.4 in.	15.3 in.	28.6 in.	64.860 lbs	9.442 ft³
Metric	83.3 cm	30.0 cm	58.9 cm	94.9 cm	38.7 cm	72.7 cm	29.420 kgs	0.267 m³



Related Products & Accessories: ICBA SH, Stainless (51100.0500)



1SH STAND, CE 220-240V INF SERIES

Product #: 27825.0300



2SH STAND, CE 220-240V INF SERIES

Product #: 27875.0300



WATER FILTER, EQHP-10L

Product #: 39000.0001



Product #: 39000.0004




KIT, DRIP TRAY INF TWIN SH

Product #: 53452.0000



KIT, DRIP TRAY SINGLE

Product #: 53452.0001



FUNNEL ASSY, SMART **COFFEE BLK-CLEARED**

Product #: 53463.0038



SYSTEM, WQ-55(2)5L

Product #: 56000.0001



SYSTEM, WQ-55(2)5

Product #: 56000.0004



Product #: 56000.0024



SYSTEM, WEQ-10(1.5)5

Product #: 56000.0027



CARTRIDGE, WQ-55(2)5L

Product #: 56000.0101



CARTRIDGE, WQ-55(2)5

Product #: 56000.0104



CARTRIDGE, WEQ-10 (1.5)5L

Product #: 56000.0121



(1.5)5

Product #: 56000.0122



Serving & Holding Options: ICBA SH, Stainless(51100.0500)



